




## 103 Union elbow, taper seat


- Torque and notes for installation please find in "Technical Product Notes".
- 374 G ... refers to the thread size G according to ISO 228 of the union nut 374.



| EN | B/G | Dim.<br>[inch] | 374 G<br>[inch] | Code               | a<br>[mm] | b<br>[mm] | c<br>[mm] | s1<br>[mm] | s2<br>[mm] |
|----|-----|----------------|-----------------|--------------------|-----------|-----------|-----------|------------|------------|
| -  | B   | 1/2            | 1               | <b>770 103 104</b> | 76        | 39        | 40.5      | 25         | 39         |
| -  | G   | 1/2            | 1               | <b>770 103 204</b> | 76        | 39        | 40.5      | 25         | 39         |
| -  | B   | 3/4            | 1 1/4           | <b>770 103 105</b> | 81        | 43        | 42.5      | 32         | 48         |
| -  | G   | 3/4            | 1 1/4           | <b>770 103 205</b> | 81        | 43        | 42.5      | 32         | 48         |
| -  | B   | 1              | 1 1/2           | <b>770 103 106</b> | 93        | 52        | 47.5      | 38         | 55         |
| -  | G   | 1              | 1 1/2           | <b>770 103 206</b> | 93        | 52        | 47.5      | 38         | 55         |



## 120 Elbow 45°, ISO/EN A1/45°



| EN | B/G | Dim.<br>[inch] | Code               | a<br>[mm] | z<br>[mm] |
|----|-----|----------------|--------------------|-----------|-----------|
| •  | B   | 3/8            | <b>770 120 103</b> | 20        | 10        |
| •  | G   | 3/8            | <b>770 120 203</b> | 20        | 10        |
| •  | B   | 1/2            | <b>770 120 104</b> | 22        | 9         |
| •  | G   | 1/2            | <b>770 120 204</b> | 22        | 9         |
| •  | B   | 3/4            | <b>770 120 105</b> | 25        | 10        |
| •  | G   | 3/4            | <b>770 120 205</b> | 25        | 10        |
| •  | B   | 1              | <b>770 120 106</b> | 28        | 11        |
| •  | G   | 1              | <b>770 120 206</b> | 28        | 11        |
| •  | B   | 1 1/4          | <b>770 120 107</b> | 33        | 14        |
| •  | G   | 1 1/4          | <b>770 120 207</b> | 33        | 14        |
| •  | B   | 1 1/2          | <b>770 120 108</b> | 36        | 17        |
| •  | G   | 1 1/2          | <b>770 120 208</b> | 36        | 17        |
| •  | B   | 2              | <b>770 120 109</b> | 43        | 19        |
| •  | G   | 2              | <b>770 120 209</b> | 43        | 19        |
| -  | B   | 2 1/2          | <b>770 120 110</b> | 48        | 21        |
| -  | G   | 2 1/2          | <b>770 120 210</b> | 48        | 21        |
| -  | B   | 3              | <b>770 120 111</b> | 54        | 24        |
| -  | G   | 3              | <b>770 120 211</b> | 54        | 24        |