


BIS Reduktionsmuffe (M/F)

(K 55 35)


justering af gevindtilslutning



647 3 XXX




647 3 521



Funktioner og fordele

■ for at forstørre eller reducere gevindstørrelsen på rørbøjler, mm.

- materiale: stål
- elforzinket
- brandtestet



Art.nr.	VVS nr.	H (mm)	h (mm)	G1	G2	Lm1 (mm)	Lm2 (mm)	SW1 (mm)	Pakke1	Pakke2
647 3 008	018049806	19	12	M8	M6	7,0	5,5	13	100	1.000
647 3 206	018049808	20	12	M6	M8	7,0	6,0	13	100	2.000
647 3 210	018049830	23	15	M10	M8	9,0	6,0	13	100	2.000
647 3 212	018049832	23	15	M12	M8	8,0	6,0	17	50	-
647 3 221	018049834	30	22	G1/2	M8	13,0	8,0	27	50	250
647 3 306	018039006	21	13	M6	M10	7,0	6,0	13	100	-
647 3 308	018049810	21	13	M8	M10	7,0	6,0	13	100	2.000
647 3 312	018039012	25	15	M12	M10	8,0	8,0	17	50	500
647 3 316	018039016	32	22	M16	M10	13,0	8,0	24	50	-
647 3 321	018049811	31	21	G1/2	M10	12,0	8,0	27	25	250
647 3 408	018039038	23	13	M8	M12	7,0	7,5	13	50	1.000
647 3 410	018049812	23	13	M10	M12	8,0	7,5	13	50	1.000
647 3 416	018039046	32	22	M16	M12	11,0	8,0	24	50	-
647 3 510	018039070	32	18	M10	M16	9,0	11,0	19	50	-
647 3 512	018039072	32	18	M12	M16	10,0	11,0	19	50	-
647 3 521		15	-	1/2"	M16	15,0	-	-	50	250
647 3 421		26	11	M10	G1/2	9,0	13,0	27	25	250
647 3 621		25	15	G3/4	G1/2	12,0	7,0	-	50	700
647 3 721		32	20	G1	G1/2	17,0	9,0	-	10	100

M10 og derover er brandtestet.

