



Muffe N82

Muffe, halv, med cylindrisk whitworth/BSP gevind
Half socket, with cylindrical whitworth/BSP thread

Tryktrin / Pressure: 40 bar

Cert.: EN 10204/3.1

Dim.	L mm	D mm	Kg/ stk/pc	AISI 316	Varenr. Article no.
1/8"	10,0	14,0	0,009	●	10202
1/4"	11,0	18,5	0,010	●	10203
3/8"	12,0	21,3	0,015	●	10204
1/2"	15,0	26,5	0,029	●	10205
3/4"	17,0	32,5	0,054	●	10206
1"	19,5	39,5	0,076	●	10207
1 1/4"	22,0	48,3	0,116	●	10208
1 1/2"	22,0	54,5	0,138	●	10209
2"	26,0	66,3	0,218	●	10210
2 1/2"	30,0	82,0	0,273	●	10211
3"	34,0	95,0	0,328	●	10212





Muffe N82 støbt / casted

Muffe, halv, med cylindrisk whitworth/BSP gevind
Half socket, with cylindrical whitworth/BSP thread

Tryktrin / Pressure: 150 lbs / 10 bar

Cert.: EN 10204/3.1

Dim.	L mm	D mm	Kg/ stk/pc	AISI 316	Varenr. Article no.
1/8"	11,0	14,0	0,010	●	24156
1/4"	13,0	19,0	0,015	●	24157
3/8"	14,0	22,0	0,020	●	24158
1/2"	18,0	27,0	0,030	●	24159
3/4"	19,0	32,0	0,047	●	24160
1"	21,0	40,0	0,054	●	24161
1 1/4"	23,0	49,0	0,195	●	24162
1 1/2"	23,0	55,0	0,120	●	24163
2"	27,0	67,0	0,155	●	24164
2 1/2"	32,0	83,0	0,340	●	24165
3"	35,0	95,0	0,325	●	24166





Muffe N83

Muffe, med cylindrisk whitworth/BSP gevind
Socket, with cylindrical whitworth/BSP thread

Tryktrin / Pressure: 40 bar

Cert.: EN 10204/3.1

Dim.	L mm	D mm	Kg/ stk/pc	AISI 316	Varenr. Article no.
1/8"	17,0	14,0	0,011	●	10213
1/4"	25,0	18,5	0,025	●	10214
3/8"	26,0	21,3	0,039	●	10215
1/2"	34,0	26,5	0,074	●	10216
3/4"	36,0	32,5	0,112	●	10217
1"	43,0	39,0	0,158	●	10218
1 1/4"	48,0	48,3	0,265	●	10219
1 1/2"	48,0	54,5	0,314	●	10220
2"	56,0	66,3	0,532	●	10221
2 1/2"	65,0	82,0	0,795	●	10222
3"	71,0	95,0	1,060	●	10223
4"	85,0	125,0	3,000	●	10224



Muffe N83 støbt / casted

Muffe, med cylindrisk whitworth/BSP gevind
Socket, with cylindrical whitworth/BSP thread

Tryktrin / Pressure: 150 lbs / 10 bar

Cert.: EN 10204/3.1

Dim.	L mm	D mm	Kg/ stk/pc	AISI 316	Varenr. Article no.
1/8"	20,0	14,0	0,015	●	24171
1/4"	25,0	18,5	0,025	●	24172
3/8"	26,0	21,5	0,033	●	24173
1/2"	34,0	26,5	0,064	●	24174
3/4"	36,0	32,0	0,090	●	24175
1"	43,0	39,5	0,150	●	24176
1 1/4"	48,0	48,5	0,200	●	24177
1 1/2"	48,0	54,5	0,240	●	24178
2"	56,0	66,5	0,360	●	24179
2 1/2"	65,0	82,5	0,750	●	24180
3"	71,0	95,0	0,780	●	24181
4"	83,0	123,0	1,460	●	24182

