

Nippel N72



Nippel, med cylindrisk whitworth/BSP gevind

Parallel nipple, with cylindrical whitworth/BSP thread

Tryktrin / Pressure: 40 bar

Cert.: EN 10204/3.1

Dim.	L mm	Kg/ stk/pc	AISI 316	Varenr. Article no.
1/8"	16,0	0,004	●	10079
1/4"	18,0	0,008	●	10080
3/8"	22,0	0,017	●	10081
3/8"	25,0	0,020	●	32380
1/2"	25,0	0,021	●	10082
1/2"	30,0	0,030	●	32381
3/4"	30,0	0,029	●	10083
1"	30,0	0,070	▶	32382
1"	35,0	0,055	●	10084
1 1/4"	38,0	0,076	●	10085
1 1/2"	38,0	0,106	●	10086
2"	40,0	0,140	●	32383
2"	45,0	0,140	●	10087
2 1/2"	55,0	0,170	●	10088
3"	60,0	0,202	▶	10089



Nippel N72

Nippel, sammenskåret, med konisk whitworth/BSP gevind

Nipple, with taper whitworth/BSP thread

Tryktrin / Pressure: 40 bar

Cert.: EN 10204/3.1

Dim.	L mm	Kg/ stk/pc	AISI 316	Varenr. Article no.
1/4"	25,0	0,015	●	32968
3/8"	25,0	0,026	●	32969
1/2"	30,0	0,042	●	32970
3/4"	30,0	0,055	●	32971
1"	30,0	0,110	●	32972
1 1/4"	40,0	0,141	●	32973
1 1/2"	40,0	0,162	●	32974
2"	40,0	0,230	●	32975

