

SANCO Kobberrør



Lige længder

EN 1057 - Hård (R290)

Størrelse Tykkelse (mm)	YD x	5m	Nominel Rørvægt (Kg/m)	Maksimalt arbejdstryk op til 65°C (bar) #	Vand indhold (l/m)

SANCO	10	x	0,8	*	0,206	70	0,055
	12	x	1,0	*	0,308	104	0,079
	15	x	1,0	*	0,391	82	0,133
	18	x	1,0	*	0,475	67	0,201
SANCO	22	x	1,0	*	0,587	54	0,314
	28	x	1,2	*	0,899	36	0,515
	35	x	1,5	*	1,410	51	0,804
	42	x	1,5	*	1,700	42	1,195
	54	x	1,5	*	2,200	23	2,040
	64	x	2,0	*	3,467	37	2,827
	70	x	2,0	*	-	-	-
	76,1	x	2,0	*	4,144	31	4,083
	88,9	x	2,0	*	4,859	26	5,661
108	x	2,5	*	3,374	27	8,332	

Rør i ringe (coils)

EN 1057 - Bløde - udglødet (R220)

Størrelse Tykkelse (mm)	YD x	Nominel Rørvægt (Kg/m)	Maksimalt arbejdstryk op til 65°C (bar) #	Vand indhold (l/m)	Ringe pr. palle

SANCO	6	x	0,8	0,116	117	0,015	60
	8	x	0,8	0,161	88	0,032	40
	10	x	0,8	0,206	70	0,055	75
	12	x	1,0	0,308	104	0,079	35
	15	x	1,0	0,391	82	0,133	30
	18	x	1,0	0,475	67	0,201	25
	22	x	1,0	0,587	54	0,314	20