

PLASTISOLEREDE LÆNGDER OG RINGE

EN 13349 / EN 1057 - Bløde - udglødet (R220)

Størrelse Tykkelse (mm)	YD x	Total yterdiame ter incl. Isolering (mm)	Maksimalt arbejdstryk op til 65°C (bar) #	Vand indhold (l/m)	Nominel Rørvægt (Kg/m)	Leverings måde
-------------------------------	------	--	--	--------------------------	------------------------------	-------------------

WICU-rør iht. DS 2110	6	x	1,0	10,000	200	0,013	0,140	Ringe 25 eller 50 m længder 5 m - 22 mm ej 50 m
	8	x	1,0	12,000	88	0,028	0,196	
	10	x	1,0	14,000	70	0,050	0,252	
	12	x	1,0	16,000	104	0,079	0,308	
	15	x	1,0	19,000	82	0,133	0,391	
	18	x	1,0	23,000	67	0,201	0,475	
	22	x	1,0	27,000	54	0,314	0,587	
	28	x	1,0	33,000	37	0,531	0,756	Længder 5 m
	35	x	1,2	40,000	35	0,835	1,136	
	42	x	1,2	48,000	29	1,195	1,371	
54	x	1,5	60,000	23	2,040	2,200		

WICU-ECO-Danmark	12	x	1,0	33,000	90	0,079	0,308	længder 5 m
	15	x	1,0	37,000	71	0,133	0,391	
	18	x	1,0	41,000	58	0,201	0,475	
	22	x	1,0	46,000	47	0,314	0,587	
	28	x	1,0	64,000	37	0,531	0,756	
	35	x	1,2	72,000	35	0,835	1,136	
	42	x	1,2	91,000	29	1,232	1,371	
	54	x	1,5	116,000	28	2,040	2,200	
	12	x	1,0	26,000	90	0,079	0,308	ringe 25 m
	15	x	1,0	29,000	71	0,133	0,391	
	18	x	1,0	36,000	58	0,201	0,475	
	22	x	1,0	45,000	47	0,314	0,587	