


**Geberit PE bøjning**



**Anvendelse**

- Til afløb fra bygninger
- Til afvanding af grunde

**Egenskaber**

- Kan svejdes på begge sider med elektrosvejsemuffe
- UV-beständig

**Tekniske data**

Materiale PE-HD

**Artikel**

Varenr.	VVS no.	DN	d, ø [mm]	X [cm]	K [cm]	r [cm]
arc / Vinkel: 45°						
<b>360.045.16.1</b>	184036240	40	40	4	2	
<b>361.045.16.1</b>	184036250	50	50	4,5	2	
<b>363.045.16.1</b>	184036256	56	56	4,5	2	
<b>364.045.16.1</b>	184036263	60	63	5	2	
<b>365.045.16.1</b>	184036275	70	75	5	2	
<b>366.045.16.1</b>	184036290	90	90	5,5	2	
<b>367.045.16.1</b>	184036310	100	110	6	2,5	
<b>368.045.16.1</b>	184036320	125	125	6,5	2,5	
<b>369.045.16.1</b>	184036330	150	160	6,9	2	
<b>370.045.16.1</b>	184036350	200	200	18	2,5	20
arc / Vinkel: 88,5°						
<b>361.088.16.1</b>	184034250	50	50	6	2	
<b>363.088.16.1</b>	184034256	56	56	6,5	2	
<b>364.088.16.1</b>	184034263	60	63	7	2	
<b>365.088.16.1</b>	184034275	70	75	7,5	2	
<b>366.088.16.1</b>	184034290	90	90	8	2	
<b>367.088.16.1</b>	184034310	100	110	9,5	2,5	
<b>368.088.16.1</b>	184034320	125	125	10	2,5	
<b>369.088.16.1</b>	184034330	150	160	12	2,5	