


Geberit PE reduktion centrisk, kort



Anvendelse

- Til afløb fra bygninger
- Til afvanding af grunde

Egenskaber

- UV-beständig

Tekniske data

Materiale

PE-HD

Artikel

Varenr.	VVS no.	DN	d, ø [mm]	d1, ø [mm]	H [cm]	h [cm]	K [cm]
360.557.16.1	184091239	40 / 30	40	32	8	3	1,5
361.557.16.1	184091248	50 / 30	50	32	8	3	1,5
361.559.16.1	184091249	50 / 40	50	40	8	3	1,5
363.559.16.1	184091254	56 / 40	56	40	8	3	1,5
363.560.16.1	184091255	56 / 50	56	50	8	3	1,5
364.559.16.1	184091261	60 / 40	63	40	8	3	1,5
364.560.16.1	184091262	60 / 50	63	50	8	3	1,5
364.565.16.1	184091266	60 / 56	63	56	8	3	1,5
365.559.16.1	184091272	70 / 40	75	40	8	3	1,5
365.560.16.1	184091273	70 / 50	75	50	8	3	1,5
365.565.16.1	184091278	70 / 56	75	56	8	3	1,5
365.570.16.1	184091274	70 / 60	75	63	8	3	1,5
366.559.16.1	184091286	90 / 40	90	40	8	3	1,5
366.560.16.1	184091287	90 / 50	90	50	8	3	1,5
366.565.16.1	184091292	90 / 56	90	56	8	3	1,5
366.570.16.1	184091288	90 / 60	90	63	8	3	1,5
366.575.16.1	184091289	90 / 70	90	75	8	3	1,5
367.559.16.1	184091305	100 / 40	110	40	8	3	1,5
367.560.16.1	184091306	100 / 50	110	50	8	3	1,5
367.565.16.1	184091300	100 / 56	110	56	8	3	1,5
367.570.16.1	184091307	100 / 60	110	63	8	3	1,5
367.575.16.1	184091308	100 / 70	110	75	8	3	1,5
367.580.16.1	184091309	100 / 90	110	90	8	3	1,5
368.575.16.1	184091317	125 / 70	125	75	8	3	1,5
368.580.16.1	184091318	125 / 90	125	90	8	3	1,5
368.585.16.1	184091319	125 / 100	125	110	8	3	1,5
369.535.16.1	184091327	150 / 100	160	110	4	0,6	