






# T-rør Type TPR



**TPR - Ø<sub>1</sub> - Ø<sub>2</sub>**  
 ↳ Afgrening  
 ↳ Hovedrør

Rustfri: RTS - Ø<sub>1</sub> - Ø<sub>2</sub>

Tryktabsværdier s.10 eller på [www.oeland.dk](http://www.oeland.dk)

Ø1 nom	Ø2 nom	H	L	Li	Vægt	Pres/Byg
mm	mm	mm	mm	mm	kg	
80 - 80	10	150	40 / 40	0,31	P	
80 - 100	30	170	40 / 40	3,40	B	
80 - 125	35	205	40 / 40	3,40	B	
80 - 160	40	250	40 / 40	3,45	B	
100 - 80	10	150	40 / 40	0,37	P	
100 - 100	10	180	40 / 40	0,45	P	
100 - 125	35	205	40 / 40	3,35	B	
100 - 160	40	250	40 / 40	3,35	B	
100 - 200	45	300	40 / 40	3,50	B	
100 - 250	55	370	40 / 40	4,00	B	
125 - 80	15	150	40 / 40	0,51	P	
125 - 100	20	180	40 / 40	0,52	P	
125 - 125	12	200	40 / 40	0,64	P	
125 - 160	40	250	40 / 40	4,00	B	
125 - 200	45	300	40 / 40	4,20	B	
125 - 250	55	370	40 / 40	4,20	B	
125 - 315	65	455	40 / 40	4,70	B	
160 - 80	15	150	40 / 40	0,61	P	
160 - 100	20	180	40 / 40	0,63	P	
160 - 125	20	200	40 / 40	0,74	P	
160 - 160	16	250	40 / 40	0,92	P	
160 - 200	45	300	40 / 40	5,10	B	
160 - 250	55	370	40 / 40	5,00	B	
160 - 315	65	455	40 / 40	5,00	B	
200 - 80	15	150	40 / 40	0,80	P	
200 - 100	20	180	40 / 40	0,84	P	
200 - 125	20	200	40 / 40	1,00	P	
200 - 160	30	250	40 / 40	1,20	P	
200 - 200	25	310	40 / 40	1,40	P	
200 - 250	55	370	40 / 40	5,00	B	
200 - 315	65	455	40 / 40	5,50	B	
200 - 400	80	570	40 / 65	5,50	B	
250 - 80	15	150	40 / 40	0,96	P	
250 - 100	15	180	40 / 40	1,00	P	

Ø1 nom	Ø2 nom	H	L	Li	Vægt	Pres/Byg
mm	mm	mm	mm	mm	kg	
250 - 200	20	310	40 / 40	1,80	P	
250 - 250	30	380	40 / 40	2,10	P	
250 - 315	65	455	40 / 40	5,75	B	
250 - 400	80	570	40 / 65	6,50	B	
250 - 500	95	700	40 / 65	7,50	B	
315 - 80	15	150	40 / 40	1,20	P	
315 - 100	15	180	40 / 40	1,30	P	
315 - 125	15	200	40 / 40	1,50	P	
315 - 160	25	250	40 / 40	1,70	P	
315 - 200	25	310	40 / 40	2,10	P	
315 - 250	20	380	40 / 40	2,60	P	
315 - 315	20	430	40 / 40	2,90	P	
315 - 400	80	570	40 / 65	8,50	B	
315 - 500	95	700	40 / 65	10,25	B	
315 - 630	115	870	40 / 65	11,00	B	
400 - 100	15	180	65 / 40	2,50	P	
400 - 125	15	200	65 / 40	2,70	P	
400 - 160	20	250	65 / 40	3,00	P	
400 - 200	20	310	65 / 40	3,30	P	
400 - 250	30	380	65 / 40	3,90	P	
400 - 315	25	430	65 / 40	4,20	P	
400 - 400	32	570	65 / 65	5,90	B	
400 - 500	95	700	65 / 65	11,00	B	
400 - 630	115	870	65 / 65	13,00	B	
500 - 100	15	180	65 / 40	3,00	P	
500 - 125	15	200	65 / 40	3,30	P	
500 - 160	20	250	65 / 40	3,70	P	
500 - 200	20	310	65 / 40	4,10	P	
500 - 250	30	380	65 / 40	4,80	P	
500 - 315	25	430	65 / 40	5,20	P	
500 - 400	80	570	65 / 65	7,10	B	
500 - 500	95	700	65 / 65	8,60	B	
500 - 630	115	870	65 / 65	17,00	B	
500 - 800	145	1090	65 / 100	18,00	B	

Ø1 nom	Ø2 nom	H	L	Li	Vægt	Pres/Byg
mm	mm	mm	mm	mm	kg	
630 - 100	20	180	65 / 40	3,50	P	
630 - 125	30	200	65 / 40	3,90	P	
630 - 160	20	250	65 / 40	4,40	P	
630 - 200	20	310	65 / 40	4,90	P	
630 - 250	25	380	65 / 40	5,90	P	
630 - 315	25	430	65 / 40	6,30	P	
630 - 400	32	570	65 / 65	8,20	B	
630 - 500	95	700	65 / 65	10,00	B	
630 - 630	115	870	65 / 65	12,00	B	
630 - 710	130	970	65 / 65	21,00	B	
630 - 800	145	1090	65 / 100	21,00	B	
630 - 1000	175	1350	65 / 100	23,00	B	
710 - 400	80	570	65 / 65	13,00	B	
710 - 500	95	700	65 / 65	14,00	B	
710 - 630	115	870	65 / 65	17,00	B	
710 - 710	130	970	65 / 65	23,00	B	
710 - 800	145	1090	65 / 100	23,00	B	
710 - 1000	175	1350	65 / 100	27,00	B	
800 - 400	80	570	100 / 65	14,00	B	
800 - 500	95	700	100 / 65	15,00	B	
800 - 630	115	870	100 / 65	18,00	B	
800 - 710	130	970	100 / 65	23,00	B	
800 - 800	145	1090	100 / 100	24,00	B	
800 - 1000	175	1350	100 / 100	31,00	B	
1000 - 500	95	700	100 / 65	19,00	B	
1000 - 630	115	870	100 / 65	24,00	B	
1000 - 710	130	970	100 / 65	24,00	B	
1000 - 800	145	1090	100 / 100	25,00	B	
1000 - 1000	175	1350	100 / 100	31,00	B	
1000 - 1250	215	1680	100 / 100	41,00	B	
1250 - 630	115	870	100 / 65	29,00	B	
1250 - 710	130	970	100 / 65	33,00	B	
1250 - 800	145	1090	100 / 100	33,00	B	
1250 - 1000	175	1350	100 / 100	40,00	B	

