

PRODUCT SPECIFICATION TAPE

Article no.	:	105724/ 5030
Description	:	PROFF TAPES DUCT TAPE
Dimension	:	50 mm x 50 meter
Colour	:	Gray included branding.
Material	:	Polyethhylene/ Cloth/ hot melt adhesive
Unit	:	Handrolle
Thickness	:	230 μ -70 mesh
Total thicknes	:	240 μ (+/- 10)
Initial tack (ball test)		\geq 10 Ball nr. (GB/T 4852-2002)
Tensile Strenght		\geq 40 N/cm (GB/T 7753-1987)
180° peel adhesion(stainless steel)		\geq 11 N/25mm (GB/T 2792-1998)
Holding power (stainless steel)	:	\geq 2.0 Hrs (GB/T 4851-1998)
Storage	:	Dry storage at a temperature between 20°C - 30°C, dry 50%-70% and away from direct sunlight, and other heat sources.
Use		If the storage temperature has been different from what suggested, bring the tape back to that temperature before application, use within 6 months from date of production.
Legislation	:	The material is produced after the guidelines in the EU directive 94/62/EF and the Danish Ministry of the environment ´s executive order no. 1049/2011 about recyclable material and packing waste.
Date.	:	29. april 2015
		QA-Coordinator. Dorthe Nielsen

A handwritten signature in blue ink, appearing to read "D. Nielsen", is written over a horizontal line.

