

SI-V32-M230-3POS

Technical Specifications – Valve

- **Angular rotation**
- 90 °
- **Leakage rate**
- „Waterproof“ as per
- EN 60534-4 L/1,
- better than class 4
- **Leakage rate bypass**
- < 1 % of k_{vs} value
- **DN**
- 32
- k_{vs}
- 25 m³/h
- **Medium**
- Cooling water , Chilled water , Water
- with anti-freeze ,
- Low-temperature hot water , High-temperature hot water
- **Medium temperature**
- -10...120 °C
- **Permissible operating pressure**
- 1600 kPa
- **Material, valve body**
- Dezincification resistant
- hot-pressed brass (DZR), CW602N
- **Material, inside set**
- Dezincification resistant
- hot-pressed brass (DZR),
- CW602N, chromium-plated
- **PN class**
- PN 40
- **Connecting thread**
- Rp 1¼ "
- **GMA../GLB..9E Δp_{max}**
- 350 kPa
- **GLB..9E Δp_{max}**
- 350 kPa

Technical Specifications - Actuator

- **Torque**
- 10 Nm
- **Angular rotation**
- 90 °
- **Power consumption**
- 2 VA, 1 W
- **Positioning time**
- 150 s
- **Cable length**
- 0.9 m
- **Positioning signal**
- 3-position
- **Spring return function**
- No
- **Degree of protection**
- IP54
- **Ambient temperature, operation**
- -32...55 °C
- **Dimensions (W x H x D)**
- 88 x 112 x 143 mm
- **Mounting position**
- Upright to horizontal
- **Operating voltage**
- AC 230 V
- **Position feedback**
- DC 0...10 V (GLB161.9E)