SET LAUFEN PRO N

Floorstanding WC combination with cistern with fixing holes for floor fixation 82795.6



TECHNICAL DA	ATA
Order no.	82795.6
Certified to	EN 997
Specification	Washdown for 4,5/3-I-flush, Charge 737
	ceramic height 460 mm
	2 fixing holes
	with cistern flushing mechanism, water
	condensation insulation,
	Dual-Flush (4,5/3-l-flush), water inlet bottom
	right 1/2" brass
Outlet	vertical
Weight	38,0 kg
Accessories excl.	Seat and cover, order no. 89095.0
	Seat and cover with automatic lowering system,
	order no. 89095.1
Mounting acc. incl.	Fastening kit, order no. 89175.7
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC pan washdown LAUFEN PRO N, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)

EN 997, 4,5/3-I-flush, dimensions 360 x 650 x 920 mm $\,$

outlet vertical 70 mm

concealed fixation, ceramic height 460 mm, 2 fixing holes

Special feature: concealed surfaces directing water are fully glazed

throughout, open water rim, vacuum checked

Further options / accessories: Surface refinement LCC, WC seat and cover, ± 9095.0 , WC seat and cover with automatic lowering ± 9095.1 Order no. ± 2795.6

TECHNICAL DRAWINGS / S 1 : 20





